

Street Diesel 8000lbs

1. Street legal vehicles.
2. Truck must be registered.
3. No aftermarket turbos.
4. No Nitrous Oxide.
5. No hanging weight.
6. No dual wheels.
7. Street legal DOT tires: no cutting or grooving, etc.
8. Hitch class 3 receiver: hook point must extend out the back of vehicle. Must be visible when standing in truck bed looking down. 3" hole, 26" from ground up.
9. Rear suspension must have 1" travel.
10. Helmets must be buckled.
11. Seat Belts must be worn.
12. Fire extinguishers recommended.

ANY ENGINE MODIFICATIONS RUN IN OPEN DIESEL CLASS

ANY UNSPORTSMANLIKE CONDUCT ON OR OFF THE TRACK COULD BE SUBJECT TO DISQUALIFICATION

ANY INTERFERENCE FROM TRUCK DRIVERS, CREW OR FAMILY/FRIENDS ANYWHERE ON THE PULLING GROUNDS WILL BE GROUNDS FOR DISQUALIFICATION

Work Stock Diesel 8500lbs

1. Factory OEM Engines.
2. Modifications to engine are allowed.
3. Aftermarket turbos must have working air shut-off in rear to hook to sled tether.
4. No Nitrous Oxide.
5. Must have Full Cabs.
6. Dual wheels allowed as long as they are covered by fenders or truck body.
7. Street legal DOT tires: no cutting or grooving.
8. Axle lockers will be permitted.
9. Traction Bars are allowed.
10. Hitch: hook point must extend out the back of vehicle. Must be visible when standing in truck bed looking down. 3" hole, 26" from ground up.
11. Added Weight can be mounted on front of truck. No more than 60" forward of front axle.
12. Rear suspension must have 1" travel.
13. Helmets must be buckled.
14. Seat Belts must be worn.
15. Fire extinguishers.

ANY UNSPORTSMANLIKE CONDUCT ON OR OFF THE TRACK COULD BE SUBJECT TO DISQUALIFICATION

ANY INTERFERENCE FROM TRUCK DRIVERS, CREW OR FAMILY/FRIENDS ANYWHERE ON THE PULLING GROUNDS WILL BE GROUNDS FOR DISQUALIFICATION

Open Diesel 9000lbs

1. Factory OEM Engines.
2. Modifications to engine are allowed.
3. Aftermarket turbos must have working air shut-off in rear to hook to sled tether.
4. No Nitrous Oxide.
5. Must have Full Cabs.
6. Dual wheels allowed as long as they are covered by fenders or truck body.
7. Street legal DOT tires: no cutting or grooving.
8. Axle lockers will be permitted.
9. Traction Bars are allowed.
10. Hitch: hook point must extend out the back of vehicle. Must be visible when standing in truck bed looking down. 3" hole, 26" from ground up.
11. Added Weight can be mounted on front of truck. No more than 60" forward of front axle.
12. Rear suspension must have 1" travel.
13. Helmets must be buckled.
14. Seat Belts must be worn.
15. Fire extinguishers.

ANY UNSPORTSMANLIKE CONDUCT ON OR OFF THE TRACK COULD BE SUBJECT TO DISQUALIFICATION

ANY INTERFERENCE FROM TRUCK DRIVERS, CREW OR FAMILY/FRIENDS ANYWHERE ON THE PULLING GROUNDS WILL BE GROUNDS FOR DISQUALIFICATION